



**Dia Tolerance :**  
**+ 0.00 / - 0.015**  
**Concentricity : 0.005 max.**

**APPLICATION**

Suitable for milling Graphite, CFK/GFK, Green stage ceramic / Carbides and Non ferrous

**ADVANTAGES**

Higher dimensional accuracy  
Improved process capability  
Extreme wear resistance  
CVD Diamond coating

**PACKING**  
Single tool per pack.

Dia ød	Radius R ±0.007	EFL l	Approach Length l1	Neck Dia d1	Total Length L	Shank Dia ØD h5	Stock
0.40	0.20	0.40	4.00	0.35	55	3.00	
0.50	0.25	0.50	5.00	0.45	55	3.00	
0.50	0.25	0.50	10.00	0.45	55	3.00	
0.60	0.30	0.80	6.00	0.56	55	3.00	
0.80	0.40	1.00	8.00	0.75	55	3.00	
0.80	0.40	1.00	12.00	0.75	55	3.00	
1.00	0.50	1.00	5.00	0.90	55	3.00	
1.00	0.50	1.00	10.00	0.90	55	3.00	
1.00	0.50	1.00	20.00	0.90	55	3.00	
1.50	0.75	2.00	10.00	1.40	55	3.00	
1.50	0.75	2.00	15.00	1.40	55	3.00	
1.50	0.75	2.00	25.00	1.40	55	3.00	
2.00	1.00	2.00	10.00	1.90	55	3.00	
2.00	1.00	2.00	15.00	1.90	55	3.00	
2.00	1.00	2.00	20.00	1.90	55	3.00	
2.00	1.00	2.00	25.00	1.90	65	3.00	
2.00	1.00	2.00	30.00	1.90	65	3.00	
3.00	1.50	3.00	15.00	2.90	65	4.00	
3.00	1.50	3.00	30.00	2.90	75	4.00	
4.00	2.00	4.00	30.00	3.90	75	5.00	
6.00	3.00	6.00	30.00	5.90	75	6.00	
6.00	3.00	6.00	50.00	5.90	90	6.00	