

Dia Tolerance :
+ 0.00 / - 0.010 for $\varnothing < 4.00$
+ 0.00 / - 0.030 for $\varnothing \geq 4.00$
Concentricity: 0.010 max.

APPLICATION

Suitable for milling Graphite, CFK/GFK, Green stage ceramic / Carbides and Non ferrous

ADVANTAGES

- Higher dimensional accuracy
- Improved process capability
- Extreme wear resistance
- CVD Diamond coating

PACKING
Single tool per pack.

Dia $\varnothing d$	Corner Radius R ± 0.010	EFL l	Approach Length l1	Neck Dia d1	Total Length L	Shank Dia $\varnothing D$ h5	Stock
3.00	0.30	6.00	14.0	2.70	50	3.00	
3.00	0.30	6.00	32.0	2.70	80	3.00	
3.00	0.50	6.00	14.0	2.70	50	3.00	
3.00	0.50	6.00	32.0	2.70	80	3.00	
4.00	0.40	8.00	16.0	3.70	50	4.00	
4.00	0.50	8.00	16.0	3.70	50	4.00	
4.00	0.50	8.00	36.0	3.70	80	4.00	
4.00	1.00	8.00	16.0	3.70	50	4.00	
5.00	0.50	10.0	18.0	4.60	54	5.00	
6.00	0.50	13.0	21.0	5.50	57	6.00	
6.00	0.50	13.0	44.0	5.50	90	6.00	
6.00	1.00	13.0	44.0	5.50	90	6.00	
8.00	0.50	15.0	27.0	7.80	63	8.00	
8.00	0.50	20.0	30.0	7.80	90	8.00	
8.00	0.50	15.0	54.0	7.80	100	8.00	
8.00	0.50	15.0	80.0	7.80	120	8.00	
8.00	1.00	15.0	27.0	7.80	63	8.00	
8.00	1.00	20.0	30.0	7.80	90	8.00	
8.00	1.00	15.0	80.0	7.80	120	8.00	
8.00	1.50	20.0	30.0	7.80	90	8.00	
8.00	2.00	20.0	30.0	7.80	90	8.00	
10.00	0.50	18.0	32.0	9.20	72	10.00	
10.00	0.50	25.0	35.0	9.20	90	10.00	
10.00	0.50	18.0	60.0	9.20	100	10.00	
10.00	0.50	20.0	80.0	9.20	120	10.00	
10.00	1.00	18.0	32.0	9.20	72	10.00	
10.00	1.00	25.0	35.0	9.20	90	10.00	
10.00	1.00	18.0	60.0	9.20	100	10.00	
10.00	1.00	20.0	80.0	9.20	120	10.00	
10.00	1.50	25.0	35.0	9.20	90	10.00	
10.00	1.50	18.0	60.0	9.20	100	10.00	
10.00	2.00	25.0	35.0	9.20	90	10.00	
12.00	0.50	26.0	38.0	11.80	83	12.00	
12.00	0.50	30.0	40.0	11.80	100	12.00	
12.00	0.50	26.0	75.0	11.80	120	12.00	
12.00	0.50	24.0	80.0	11.80	120	12.00	
12.00	1.00	30.0	40.0	11.80	100	12.00	
12.00	1.00	26.0	75.0	11.80	120	12.00	
12.00	1.00	24.0	80.0	11.80	120	12.00	
12.00	1.50	30.0	40.0	11.80	100	12.00	


INDMILL G
Solid Carbide
4 Flute Endmill
Corner Radius
Diamond Coated



E2181

Dia ød	Corner Radius R ±0.010	EFL l	Approach Length l1	Neck Dia d1	Total Length L	Shank Dia ØD h5	Stock
12.00	1.50	26.0	75.0	11.80	120	12.00	
12.00	2.00	30.0	40.0	11.80	100	12.00	
12.00	2.00	26.0	75.0	11.80	120	12.00	
16.00	0.50	32.0	85.0	15.00	120	16.00	
16.00	1.00	32.0	85.0	15.00	120	16.00	
16.00	1.50	32.0	85.0	15.00	120	16.00	
16.00	2.00	32.0	85.0	15.00	120	16.00	

Dia Tolerance :
+ 0.00 / - 0.010 for $\phi < 4.00$
+ 0.00 / - 0.030 for $\phi \geq 4.00$
Concentricity: 0.010 max.



APPLICATION

Suitable for milling Graphite,
CFK/GFK, Green stage ceramic /
Carbides and Non ferrous

ADVANTAGES

Higher dimensional accuracy
Improved process capability
Extreme wear resistance
CVD Diamond coating

PACKING

Single tool per pack.

SCAN TO WEBSITE

