


Dia Tolerance :
 + 0.00 / - 0.010 for $\varnothing d < 6.00$
 + 0.00 / - 0.015 for $\varnothing d \geq 6.00$
 Concentricity : 0.005 max.



APPLICATION

Suitable for milling Graphite,
 CFK/GFK, Green stage ceramic /
 Carbides and Non ferrous

ADVANTAGES

Higher dimensional accuracy
 Improved process capability
 Extreme wear resistance
 CVD Diamond Coating
 Assured quality control

PACKING

Single tool per pack

LABELLING

Actual dia marking on label

ød	R ±0.003	l	l1	d1	L	ØD h5
0.10	0.05	0.15	0.20	0.09	60	4.00
0.10	0.05	0.15	0.40	0.09	60	4.00
0.15	0.075	0.20	0.30	0.14	60	4.00
0.15	0.075	0.20	0.60	0.14	60	4.00
0.20	0.10	0.30	1.00	0.18	60	4.00
0.20	0.10	0.30	1.50	0.18	60	4.00
0.30	0.15	0.50	0.50	0.27	60	4.00
0.30	0.15	0.50	1.00	0.27	60	4.00
0.30	0.15	0.50	1.50	0.27	60	4.00
0.30	0.15	0.50	3.00	0.27	60	4.00
0.30	0.15	0.50	4.50	0.27	60	4.00
0.30	0.15	0.50	6.00	0.27	60	4.00
0.40	0.20	0.60	2.00	0.36	60	4.00
0.40	0.20	0.60	4.00	0.36	60	4.00
0.40	0.20	0.60	6.00	0.36	60	4.00
0.40	0.20	0.60	8.00	0.36	60	4.00
0.50	0.25	0.70	2.50	0.45	60	4.00
0.50	0.25	0.70	5.00	0.45	60	4.00
0.50	0.25	0.70	7.50	0.45	60	4.00
0.50	0.25	0.70	10.00	0.45	60	4.00
0.60	0.30	1.00	3.00	0.55	60	4.00
0.60	0.30	1.00	6.00	0.55	60	4.00
0.60	0.30	1.00	9.00	0.55	60	4.00
0.60	0.30	1.00	12.00	0.55	60	4.00
0.80	0.40	1.20	4.00	0.75	60	4.00
0.80	0.40	1.20	8.00	0.75	60	4.00
0.80	0.40	1.20	12.00	0.75	60	4.00
0.80	0.40	1.20	16.00	0.75	60	4.00
1.00	0.50	1.60	5.00	0.95	60	4.00
1.00	0.50	1.60	10.00	0.95	60	4.00
1.00	0.50	1.60	15.00	0.95	60	4.00
1.00	0.50	1.60	20.00	0.95	60	4.00
1.50	0.75	2.40	5.00	1.40	60	4.00
1.50	0.75	2.40	10.00	1.40	60	4.00
1.50	0.75	2.40	15.00	1.40	60	4.00
1.50	0.75	2.40	20.00	1.40	60	4.00
2.00	1.00	3.00	6.00	1.90	60	4.00
2.00	1.00	3.00	12.00	1.90	60	4.00
2.00	1.00	3.00	18.00	1.90	60	4.00
2.00	1.00	3.00	24.00	1.90	60	4.00
2.00	1.00	3.00	30.00	1.90	60	4.00
3.00	1.50	3.50	9.00	2.90	60	6.00
3.00	1.50	3.50	14.00	2.90	60	6.00
3.00	1.50	3.50	18.00	2.90	60	6.00
3.00	1.50	3.50	24.00	2.90	60	6.00
3.00	1.50	3.50	30.00	2.90	60	6.00
3.00	1.50	3.50	35.00	2.90	70	6.00
3.00	1.50	3.50	45.00	2.90	100	6.00
4.00	2.00	4.00	12.00	3.80	60	6.00
4.00	2.00	4.00	16.00	3.80	60	6.00
4.00	2.00	4.00	24.00	3.80	60	6.00

B2001

ød	R ±0.003	l	l1	d1	L	ØD h5
4.00	2.00	4.00	30.00	3.80	60	6.00
4.00	2.00	4.00	35.00	3.80	70	6.00
4.00	2.00	4.00	40.00	3.80	100	6.00
5.00	2.50	5.00	15.00	4.80	60	6.00
5.00	2.50	5.00	30.00	4.80	60	6.00
5.00	2.50	5.00	50.00	4.80	100	6.00
6.00	3.00	6.00	18.00	5.80	60	6.00
6.00	3.00	6.00	30.00	5.80	60	6.00
6.00	3.00	6.00	35.00	5.80	70	6.00
6.00	3.00	6.00	45.00	5.80	100	6.00
6.00	3.00	6.00	60.00	5.80	100	6.00
8.00	4.00	8.00	30.00	7.70	70	8.00
8.00	4.00	8.00	80.00	7.70	140	8.00
10.00	5.00	10.00	30.00	9.70	70	10.00
10.00	5.00	10.00	100.0	9.70	150	10.00
12.00	6.00	12.00	30.00	11.70	80	12.00
12.00	6.00	12.00	100.0	11.70	150	12.00