



Dia Tolerance :
+ 0.00 / - 0.015
Concentricity : 0.005 max.

ød	R ±0.007	l	l1	d1	L	ØD h5
0.40	0.20	0.40	4.00	0.35	55	3.00
0.50	0.25	0.50	5.00	0.45	55	3.00
0.50	0.25	0.50	10.00	0.45	55	3.00
0.60	0.30	0.80	6.00	0.56	55	3.00
0.80	0.40	1.00	8.00	0.75	55	3.00
0.80	0.40	1.00	12.00	0.75	55	3.00
1.00	0.50	1.00	5.00	0.90	55	3.00
1.00	0.50	1.00	10.00	0.90	55	3.00
1.00	0.50	1.00	15.00	0.90	55	3.00
1.00	0.50	1.00	20.00	0.90	55	3.00
1.50	0.75	2.00	10.00	1.40	55	3.00
1.50	0.75	2.00	15.00	1.40	55	3.00
1.50	0.75	2.00	25.00	1.40	55	3.00
2.00	1.00	2.00	10.00	1.90	55	3.00
2.00	1.00	2.00	15.00	1.90	55	3.00
2.00	1.00	2.00	20.00	1.90	55	3.00
2.00	1.00	2.00	25.00	1.90	65	3.00
2.00	1.00	2.00	30.00	1.90	65	3.00
3.00	1.50	3.00	15.00	2.90	65	4.00
3.00	1.50	3.00	30.00	2.90	75	4.00
4.00	2.00	4.00	30.00	3.90	75	5.00
6.00	3.00	6.00	30.00	5.90	75	6.00
6.00	3.00	6.00	50.00	5.90	90	6.00

APPLICATION
Suitable for milling Graphite,
CFK/GFK, Green stage ceramic /
Carbides and Non ferrous

ADVANTAGES
Higher dimensional accuracy
Improved process capability
Extreme wear resistance
CVD Diamond Coating

PACKING
Single tool per pack