


Dia Tolerance :  
+ 0.00 / - 0.010 for  $\phi < 4.00$   
+ 0.00 / - 0.030 for  $\phi \geq 4.00$   
Concentricity : 0.010 max.



$\phi d$	R $\pm 0.010$	l	$l_1$	d1	L	$\phi D$ h5
4.00	0.50	6.00	10.00	3.80	60	6.00
6.00	0.50	9.00	20.00	5.80	60	6.00
6.00	0.50	9.00	60.00	5.80	100	6.00
6.00	1.00	9.00	20.00	5.80	60	6.00
6.00	1.00	9.00	60.00	5.80	100	6.00
8.00	1.00	12.00	30.00	7.80	90	8.00
8.00	1.00	12.00	80.00	7.80	140	8.00
10.00	1.00	20.00	30.00	9.80	100	10.00
10.00	1.00	20.00	100.0	9.80	150	10.00
12.00	1.00	24.00	30.00	11.80	100	12.00
12.00	1.00	24.00	100.0	11.80	150	12.00

**APPLICATION**

Suitable for milling Graphite,  
CFK/GFK, Green stage ceramic /  
Carbides and Non ferrous

**ADVANTAGES**

Higher dimensional accuracy  
Improved process capability  
Extreme wear resistance  
CVD Diamond Coating

**PACKING**

Single tool per pack